

S SERIGRAFIA | SCREEN PRINTIN

Serie Series





Applications	paper, coated paper, melamminic paper, cardboard	
Main features	One-component Ink.	
	Fast drying, excellent resistance to abrasion, satin finish, good opacity.	
Outdoor resistance	Not suitable for printed objects destined to long-term outdoor exposures (3-5 years).	
Mechanical and chemical solidity	Good resistance to alcohol, scratches and abrasion.	
Drying process	5-10 minutes at room temperature (20°C) and according to the working conditions.	
Colour range	Refer to the TWO-COMPONENT, "INK SYSTEM", METALLIC colour card.	
	Colours B75, B76, B77, B79, 79-010, 79-020, 79-030, 79-050 must be prepared with their respective pastes according to below scheme:	
	Gold Pastes	CA (70 TR) 1:3 – 4
	Silver Pastes B79	CA (70 TR) 1:4 – 5
	Other Silver Pastes	CA (70 TR) 1:6 – 7
	The metallic colours RE and ME are not available.	
	It is always recommended to carry out preventive overprinting tests.	
Auxiliaries and additives	Fast thinner	VS
	Medium thinner	XL-DM
	Slow thinner	VH
	Retarding paste	5-10%
	Spreader M 2000	0,5%
	Antisilicone	0,5%
	Unuversal anti-foam agent	0,5%
Ink removal	Sericom DACS solvent	
	"Lavaggio Telai" solvent	

PRODUCT CLASSIFICATION:

The CA Series inks ar classified as NT (non-toxic) and are formulated with pigments which are free from heavy metals. Safety Data Sheets are available, according to UE regulation. Main indications are carried on the product label.

Not suitable for contact with food (not conform to FDA).

NOTE:

Our technical consultancy, carried out by word, by writing or through tests and experiments, is based on our best knowledge.

Said consultancy, however, must be considered as pure information with no binding value, even when regarding eventual property rights of third parties.

This does not exempt the customer from carrying out his own controls on our products, in order to check their suitability or not for the processes and purposes required.

Representado por: